

AGT 143-5.5-115 cm MOTOCOSITTOARE



MOTOR

Tip:
Model:
Filtru de aer:
Capacitate cilindrica:
Putere maxima:
Combustibil:
Capacitate rezervor:
Pornire:
Consum maxim:

HONDA

OHV, un cilindru, 4 timpi, racire cu aer
GX 160
in baie de ulei
163 cm³
5,5 HP
Benzina fara plumb
3,1 l
Cu demaror mecanic
1,4 l/h

MOTOCOSITTOARE:

Ambreiaj:	multidisc cu control manual, inversat
Cutie de viteze:	in baie de ulei, 6 viteze (3 viteze inainte + 3 viteze inapoi)
Dispozitive de siguranta:	maneta de ambreiaj cu dubla actiune si debreiere in cazul pierderii controlului asupra masinii (fara oprirea motorului)
Priza de putere:	independenta cu sistem de cuplare rapida
Maneta de marsarier:	montata pe ghidon (asigura schimbarea directiei de deplasare fara a fi nevoie sa schimbati viteza)
Ghidonul:	reglabil in inaltime sistem antivibratii
Transmisie:	Profesionala, in baie de ulei
Bara de taiere SF sau SP:	115 cm
Roti motoare:	Pneumatice 4 - 8", ecartament fix
Masa:	115 kg

6 viteze (3 inainte + 3 inapoi) km/h

1.05	1	1R	1.11
2.20	2	2R	2.32
3.63	3	3R	3.83

Dimensiuni (mm)

L1	1660 (1665)
L2	900 (950)
L3	760
H1	1250-400
W1	950-1450
W2	437

