

GF3 GX270 - 127 SP / 127 SF / 147 SP / 144 SF
MOTOCOASĂ



MOTOR

Tip:
Model:
Filtru de aer:
Capacitate cilindrica:
Putere maxima:
Combustibil:
Capacitate rezervor:
Pornire:
Consum:

HONDA

OHV, un cilindru, 4 timpi, racire cu aer
GX 270
in baie de ulei
270 cm³
9,0 HP
Benzina fara plumb
5,3 l
cu demaror mecanic
2,4 l/h la 6.8 CP la 3600 rpm

MOTOCOASA:

Ambreiaj:	conic cu control inversat
Cutia de viteze:	in baie de ulei, 6 viteze (3 inainte+3 inapoi)
Viteze:	1°: 1,3 km/h - 2°: 2,4 km/h - 3°: 3.6 km/h 1°R: 1,3 km/h - 2°R: 2,4 km/h - 3°R: 3,6 km/h
Dispozitive de siguranta:	debreiere automata in cazul pierderii controlului asupra masini (fara oprirea motorului);
Priza de putere:	independenta, 965 rpm cu motorul la 3600 rpm
Ghidonul:	reglabil in lateral si in inaltime
Roti motoare:	pneumatice 4.00-10", ecartament reglabil
Transmisie:	profesionala, in baie de ulei
Bara de taiere:	127 cm SP (iarba) / SF (paioase) 147 cm SP (iarba) / 144 cm SF (paioase)
Greutate:	115 kg