

WHP 30 HKX MOTOPOMPA DE PRESIUNE



MOTOR

Tip:
Model:
Putere maximă [CP]:
Diametru piston x cursă:
Capacitate cilindrică:
Compresie:
Combustibil:
Filtru de aer:
Senzor lipsa ulei:
Capacitate rezervor:
Consum:
Pornire:

HONDA

OHV, 4 timpi, racire cu aer
GX 270
9
77 x 58 mm
270 cm³
8,5 : 1
benzina fara plumb
dual
da
5.3 l
2.0 l/h la 3600 rpm
demaror mecanic

CARACTERISTICI TEHNICE POMPA

Diametru de aspiratie: 3"
Diametru de refulare: 2"1/2 + 2 x 1"1/2
Inaltimea maxima de refulare: 75,0 m
Adancimea maxima de aspiratie: 7m
Debit maxim: 44 m³/h (730 l/min)
Diametru maxim corpuri solide: 4 mm
Garnitura mecanica: SiC (carbura de siliciu)
Sistem pornire: demaror mecanic
Masa: 45 kg
Dimensiuni de gabarit: 585x485x540 mm



HONDA
ENGINES

Dotare standard:

- stuturi aspiratie si refulare din aluminiu
- piulite aspiratie si refulare din aluminiu
- garnituri aspiratie si refulare
- sorb 3"
- coliere pentru furtun
- dopuri pentru refulare

